



PDU Feed	Code
Bottom	<b>B</b>
Top	<b>T</b>



32A model :	Circuit Protection
VP24C13/12C19-32A-WSi/F_EN/2 <b>B</b> -1	Resettable Fuse x 6
VP24C13/12C19-32A-WSi/CR_EN/2 <b>T</b> -1	1-pole MCB x 6

- Input Rating : 32Amp, 400V 3PH
- Cordset : 5-wire 2 meter 4mm sq. H05V V-F cordset
- Protection : 16A resettable fuse or 16A single pole hydraulic MCB x 6
- PH-1 - Bank 1 : Output 16A max., C13 #1-7 (odd) + C19 #C1,C3
- Bank 2 : Output 16A max., C13 #2-8 (even) + C19 #C2,C4
- PH-2 - Bank 3 : Output 16A max., C13 #1-7 (odd) + C19 #C1,C3
- Bank 4 : Output 16A max., C13 #2-8 (even) + C19 #C2,C4
- PH-3 - Bank 5 : Output 16A max., C13 #1-7 (odd) + C19 #C1,C3
- Bank 6 : Output 16A max., C13 #2-8 (even) + C19 #C2,C4
- Weight : Net 12.20 Kg / Gross 14.20 Kg

Chassis Color	Code
Black	<b>1</b>
White	<b>2</b>
Red	<b>3</b>
Blue	<b>4</b>
Green	<b>5</b>
Orange	<b>6</b>
Yellow	<b>7</b>
Purple	<b>8</b>



16A model :	Circuit Protection
VP24C13/12C19-16A-WSi/F_EN/2 <b>B</b> -1	Resettable Fuse x 3
VP24C13/12C19-16A-WSi/CR_EN/2 <b>T</b> -1	1-pole MCB x 3

- Input Rating : 16Amp, 400V 3PH
- Cordset : 5-wire 2 meter 1.5mm sq. H05V V-F cordset
- Protection : 16A resettable fuse or 16A single pole hydraulic MCB x 3
- PH-1 : Output 16A max., C13 #1-8 + C19 #C1-C4
- PH-2 : Output 16A max., C13 #1-8 + C19 #C1-C4
- PH-3 : Output 16A max., C13 #1-8 + C19 #C1-C4
- Weight : Net 12.20 Kg / Gross 14.20 Kg

Standard color : Black

- Operating Temperature : -5 to 60 °C
- Storage Temperature : -25 to 65 °C
- Operating Altitude : 0 to 2,000 m
- Storage Altitude : 0 to 15,000 m
- Humidity : 8 to 95% RH, non-condensing

- Meter Features ( WSi Switched PDU + Outlet Measurement )**
- Local Display : Field replaceable 2.8" color LCD with touchscreen
  - Bank Measurement : Current ( A ), Energy ( kWh ), Voltage ( V ) & Power factor
  - Outlet Measurement : Current ( A ), Energy ( kWh )
  - Outlet Control : Outlet Switch ON / OFF
  - Accuracy : ±1% Billing-grade
  - IP Access : via IP dongle, one IP Access up to 16 PDU Levels
  - Cascade : Up to 16 PDU under single IP address via IP dongle
  - SNMP : V2 / V3 via IP dongle
  - Sensor Port x 2 : Temp. Sensor / Temp. + Humid. Sensor

- EMC Compliance : CE / EMC certified
- Safety Compliance : CE / LVD certified
- Environment Compliance : RoHS2 & REACH

**AUSTIN HUGHES**  
Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2020 Austin Hughes Electronics Ltd. All rights reserved.

- Product Dimension : 85 (W) x 90 (D) x 1800 (H) mm
- Packing dimension : 110 (W) x 268 (D) x 2168 (H) mm

## Lockable IEC Outlet

- Patented design for InfraPower PDU



C13 Outlet



C19 Outlet

## Lockable IEC Cable

- Patented design of InfraPower PDU
- Low cost, easy to lock & secure
- Proprietary for lockable IEC outlet
- Applicable to standard IEC outlet
- 6 colors & 3 lengths available
- Custom color & length on request
- VDE & ENEC approval

### C13 - C14

H05VV-F 3G 0.75mm<sup>2</sup>

Cable Color	0.5M	1M	2M
Black	✓	✓	✓
Grey	✓	✓	✓
Red	✓	✓	✓
Blue	✓	✓	✓
Green	✓	✓	✓
Orange	✓	✓	✓



### C19 - C20

H05VV-F 3G 1.5mm<sup>2</sup>

Cable Color	1M	2M
Black	✓	✓
Grey	✓	✓
Red	✓	✓
Blue	✓	✓
Green	✓	✓
Orange	✓	✓



C13 - C14

lockable cable

C19 - C20

- ✓ low cost
- ✓ easy to lock
- ✓ secure

