



PDU specification drawing

1-Phase 230V 32A metered PDU : C19 x 4



32A model :	Fuse	MCB
H4C19-32A-MD/F_EN/3B-1	2	-
H4C19-32A-MD/CR_EN/3B-1	-	2



Input Rating : 32A, 230V
Inlet : 32A IEC60309 2P+E plug
Cordset : 3 meter 4mm sq. H05V V-F cordset
Protection : 16A resettable fuse or 16A hydraulic MCB x 2
Circuit Details : < **Circuit A** > Output 16A max. C 19 # C 1 - C 2
< **Circuit B** > Output 16A max. C 19 # C 3 - C 4

Single phase metered PDU
Outlet : 16A Rated IEC320 C19 x 4

AUSTIN
HUGHES Design. Manufacturing. Global Services.

The company reserves the right to modify product specifications without prior notice and assumes no responsibility for any error which may appear in this publication.

Copyright 2016 Austin Hughes Electronics Ltd. All rights reserved.

Meter Features (MD metered PDU)
Local Display : 3-digit LED ammeter measuring input load current
Measurement : Current (A)
Accuracy : ± (3% of the reading + 5 digits) RMS

EMC Compliance : FCC & CE certified
Safety Compliance : CE / LVD certified
Environment Compliance : RoHS2 & REACH

Operating Temperature : -5 to 60 °C
Storage Temperature : -25 to 65 °C
Operating Altitude : 0 to 2,000 m
Storage Altitude : 0 to 15,000 m
Humidity : 8 to 95% RH, non-condensing

Dimension : 437.5 (W) x 120 (D) x 44.5 (H) mm
Material : Steel
Color : Black (chassis)