



**Single phase basic PDU**

Input Rating : 32A, 230V  
 Outlet : 10A Rated C13 x 4  
           10A Rated AS/NZS 3112 Aussie x 20  
 Inlet : 32A IEC60309 2P+E plug  
 Cordset : 3 meter 4mm sq. H05V V-F cordset  
 Protection : 32A single pole thermal-magnetic MCB x 1  
               (10KA, C curve, IEC 60898)  
 Circuit Details : Output 32A max., C 13 #1 - 4 + AU #5 - 24

EMC Compliance	:	CE / EMC certified
Safety Compliance	:	CE / LVD certified
Environment Compliance	:	RoHS2 & REACH
Operating Temperature	:	-5 to 60 °C
Storage Temperature	:	-25 to 65 °C
Operating Altitude	:	0 to 2,000 m
Storage Altitude	:	0 to 15,000 m
Humidity	:	8 to 95% RH, non-condensing
Chassis Material	:	Steel
Chassis Color	:	Black
Product Dimension	:	54 (W) x 80 (D) x 1300 (H) mm
Net Weight	:	-
Packing Dimension ( for 2 PDUs )	:	110 (W) x 268 (D) x 1793 (H) mm
PDU Gross Weight ( for 2 PDUs )	:	-