

Cat6 KVM



Options

- DC power options : 12V / 24V / 48V / 125V
- Dual power with failover

Benefits

- Cat6 KVM with 8, 16 or 32 ports in 1U
- Cat6 dongle available for DP, HDMI, DVI-D or VGA video input
- Local console & KVM ports support resolution up to 1920 x 1200
- Multi-platform for PC, server, Blade Server & SUN / MAC
- Port switching via OSD, front button & keyboard hotkeys
- Multi lingual OSD menu
- Hot pluggable, no software or drivers required
- Cascade levels up to 8 KVM switches



DG-100P

DP-USB dongle

DG-100H

HDMI-USB dongle

DG-100SD

DVI-USB dongle


DG-100S

VGA-USB dongle


DG-100

VGA-PS/2 dongle


Basic Models - local console x 1



U-801




U-1601




U-3201

KVM Port	
Port # :	8, 16 or 32
Connector :	RJ-45
Connectivity :	DP / HDMI / DVI-D / VGA dongle via Cat6 / Cat5 cable to server up to 40 meters (132 feet)
Resolution :	16:10 - max. 1920 x 1200 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200
Local Console	
Graphic Connector :	1 x DB-15 VGA
Input device :	2 x USB type A for keyboard & mouse
Resolution :	16:10 - max. 1920 x 1200 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200


IP Models - local console + IP console



U-IP802



U-IP1602



U-IP3202


IP Console	
Connector :	RJ45
User management :	1 x active user, 15-user login
Network protocol :	DHCP / BOOTP / DNS
Security :	SSL v3, RSA, AES, HTTP / HTTPS, CSR
Browser :	Internet Explorer
Resolution :	4:3 - max. 1600 x 1200

**** IP console upgrade option for resolution support 1920 x 1080**


Remote Models - local console + remote console



U-802




U-1602




U-3202

Remote Console	
Connector :	RJ45
Connection :	via Cat5 / Cat6 cable to receiver box
Receiver box I/O :	VGA + 2 x USB type A for keyboard & mouse
Resolution :	16:9 - (1920 x 1080) Max. 50 meters 16:10 - (1920 x 1200) Max. 50 meters 16:10 - (1440 x 900) Max. 100 meters 4:3 - (1600 x 1200) Max. 100 meters 4:3 - (1280 x 1024) Max. 150 meters
 Receiver box	


Local console & KVM port connection



IP console connection




Remote console connection



KVM Cascade

- 8-level cascade up to 256 servers
- KVM cascade via CBC-6
- Level 2 - 8 KVM must be basic models :
U-801 / U-1601 / U-3201
- 1st level KVM takes all control of slave KVMs



Management

Port switching	OSD, front button & keyboard hotkeys
Expansion	8-level cascade up to 256 servers

Compatibility

Hardware	HP / IBM / Dell PC, Server and Blade Server SUN / Mac
OS support	Windows / Linux / Unix / Mac OS

Environment

Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Power

Input	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption	Max. 22W

Compliance

Safety	cUL, FCC & CE certified
Environment	RoHS2 & REACH compliant

Physical

Product (W x D x H)	443 x 171 x 44 mm
	17.4 x 6.7 x 1.73 inch
Packing (W x D x H)	500 x 400 x 90 mm
	19.7 x 15.7 x 3.5 inch
Weight	Net 2.5 kg / 5.5 lb
	Gross 5.4 kg / 11.9 lb
Chassis color	Dark
Chassis materials	Steel