## Infra Cool®

## Intelligent ( Master IP ) 1U Fan Tray



F© (E

## **Benefits**

- ▶ 1U rackmount w/ 6 or 9 fans
- Cascade ports for daisy chain up to 16 levels via Cat6 cable
- Designed for low noise & high airflow performance
- 1 x intelligent Master IP fan unit allows access to 16 fan unit levels over internet
- Free ICM-02 management software remote access up to 480 fan units
- Auto & manual CFM setting reduces power consumption
- 1 x bundled temp. sensor with 2M wire
- Temperature sensing technology adjusts the fan speeds accordingly
- Unit or individual fan on / off ( remote or local )
- 48V, 24V or 12VDC power option
- 2-year standard warranty (upgradable up to 5 years)


## **Product Specifications**

	MRF-1.6	MRF-1.9
No. of Fan	6	9
Mounting	1U	1U
Unit CFM ( approx. )	648 CFM	972 CFM
Individual Fan CFM	108 CFM	
Individual Fan ON / OFF	Yes	
CFM Level	Normal / High / Max.	
IP Remote Access	Yes	
Daisy Chain Level	1st level, Intelligent ( Slave ) Fan for level 2 - 16	
MTBF	50,000 hrs	
Individual Fan Noise Level	41 dB	

Physical		MRF-1.6	MRF-1.9
Dimensions (WxDxH)	Product	480 x 458 x 44 mm 18.9 x 18 x 1.73 inch	480 x 623 x 44 mm 18.9 x 24.5 x 1.73 inch
	Packing	550 x 550 x 120 mm 21.7 x 21.7 x 4.7 inch	550 x 730 x 120 mm 21.7 x 28.7 x 4.7 inch
Weight	Net	6.8 kg / 15 lb	9 kg / 19.8 lb
	Gross	8 kg / 17.6 lb	11 kg / 24.2 lb
Casing Color		Black	

Power	MRF-1.6	MRF-1.9
Consumption	40W	60W
Input	Auto-sensing 100V or 240V AC at 50 or 60Hz via IEC cord	





Temperature Sensor		
Temperature Port	1 x temperature sensor port ( sensor bundled )	
Measurement Range	0 to 99.9°C	
Measurement Accuracy	+/- 1.5%	
Temperature Alarm	Yes	

Environment	
Operating	0 to 50°C
Storage	-5 to 60°C
Relative Humidity	90%, non-condensing
Shock	50G acceleration ( 11ms, half-sine wave )
Vibration	58~100Hz / 0.98G ( 11ms / cycle )

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS3 & REACH compliant

