



A high-resolution, quad-head KVM extender. High-definition video, transparent full-speed USB 2.0 and audio are transmitted on a single CATx or fiber cable.

A high performance KVMA extender that is designed to provide reliable and real-time access to critical computers while maintaining the same user desktop experience. Developed for enterprise organizations and high-pressure control rooms, it combines the simplicity of true plug and play and high performance 4K KVM extension for superior functionality and flexibility.

ADDERLink® XD C650 T

Extenders

Features

Quad-Head High-Definition Video

Supports quad-head 1920x1200@60Hz or single head 4096x2160@60Hz (DCI 4K60). Quad-head enabled over a single cable using DisplayPort 1.2 Multi-Stream Transport (MST) technology.

Up to 4km Extension

Supports both copper and fiber interfaces. Provides a range of up to 100m/328ft over a CAT6 cable link, and up to 4km/2.5 miles over an optical fiber link (Fiber SFP modules sold separately).

Emulated and Hi-Speed USB 2.0

USB 2.0 emulation ensures reliable connection of full and low speed HID devices (mouse or keyboard). Mass storage devices and isochronous devices, such as webcams and audio headsets can also be used through the transparent USB 2.0 Hi-Speed port.

Plug and Play

Uses a low-latency point-to-point protocol over a single CATx or fiber cable that works as soon as it is connected. No network set-up, driver or software is required.



Digital Audio over DisplayPort

Supports two channels of 24-bit, 192kHz sampled PCM audio over the DisplayPort connection.

Analog Audio

Plug analog line in/out and headphones directly into the receiver. Audio is transmitted as bi-directional stereo 24-bit/96kHz using either an analog or USB connection to the host.

Monitor Flexibility

EDID management allows the monitor capabilities to be passed back to the host computer for optimum compatibility. Additionally, a local monitor may be connected at the transmitter side.

Serial communications

RS232 can be passed between the units to a maximum rate of 115200 baud with RTS/CTS flow control.

Video Information (1 Screen)		
Maximum Resolution (1 Screen)		4096 x 2160
Frame Rate (1 Screen)		60 Hz
Color Depth (1 Screen)		8 bpc
Video Information (2 Screen)		
Maximum Resolution (2 Screens)		2560 x 1600
Frame Rate (2 Screens)		60 Hz
Color Depth (2 Screen)		8 bpc
Video Information (3 Screen)		
Maximum Resolution (3 Screens)		1920 x 1200
Frame Rate (3 Screens)		60 Hz
Color Depth (3 Screen)		8 bpc
Video Information (4 Screen)		
Maximum Resolution (4 Screens)		1920 x 1200
Frame Rate (4 Screens)		60 Hz
Color Depth (4 Screen)		8 bpc
Video Additional Information		
Video Additional Information		Supports HD60 Quad-Head or 4K60 Single-Head.
Computer Connections		
USB B		1x 2.0, True Emulation (HID Only),Full Speed
USB B		1x 2.0, Transparent,High Speed
Full Size DisplayPort		1x 1.2
Link Ports		
8p8c (RJ45)		1x
SFP+		1x
Serial Ports		
Serial Connection		1x RS232
Maximum Baud Rate		115200
Serial Additional Information		with RTS/CTS flow control
Serial Connection Type (console)		RJ12 (6p6c)
Audio Connections		
Audio Type		Analog/Digital
Channels		2x
Audio Direction		Bi-directional

Audio Additional Information		Also supports 2 channels of 24-bit/192kHz PCM audio over the DisplayPort connection.
Size (bit)		24
Speed (kHz)		96
Audio In Port		1x 3.5mm jack
Audio Out Port		1x 3.5mm jack
Cable Requirements		
CAT5e		50m / 164ft
CAT6 (SFTP)		100m / 328ft
Fiber (MM)		400m / 1312ft
Fiber (SM)		4,000m / 13123ft
Network Support		
10/100 Support		No
Power Source		
12V 3-pin		1x
Input Power Supply		PSU 18W
Power Additional Information		100-240 VAC, 47/63Hz. 12 VDC 18W output from power supply unit
Physical Design		
Construction Material		Robust metal construction
Width (mm) / (in.)		186 / 7.3
Height (mm) / (in.)		39 / 1.5
Depth (mm) / (in.)		148 / 5.8
Weight (kg) / (lb)		1.29 / 2.8
Front Panel Features		
Multi color status LEDs		4x
Compatibility		
OS Compatibility		All known operating systems



What's in the Box?

1x TX and RX pair

2x Power supply unit with country specific mains cable

1x DisplayPort® cable (VSCD18)

1x USB cable (VSC24)

1x Audio 2m/6ft cable

1x Quick start guide

Ordering Information

XD-C650P-DP-XX

ADDERLink HD quad-head transparent USB2.0 extender

Adder and the Adder logo are trademarks of Adder Technology Ltd, Cambridge, UK. All other trademarks are the property of their respective owner and may be registered in the United States Patent and Trademark Office and in other countries. Information contained in this data sheet is up-to-date and correct as at the date of issue. As Adder Technology cannot control or anticipate the conditions under which this product may be used, each user should review the information in the specific context of planned use. Images are for illustrative purposes only. Adder reserves the right to make changes to this specification without notice.