


**Benefits**

- ▶ 1U 17" 4K LED-backlit LCD console drawer
- ▶ 3840 x 2160@60Hz native resolution / 16.7M colors ( 8-bit )
- ▶ 2560 x 1440@60Hz QHD resolution support
- ▶ 1920 x 1080 & 1920 x 1200 resolution support
- ▶ Display port 1.2 video input / USB KB/MS
- ▶ Ideal for open rack / short depth rack
- ▶ 104-key USB keyboard with either touchpad or trackball
- ▶ Built-in dual stereo speakers
- ▶ One Man installation design
- ▶ Enhanced aesthetics with new molded front panel and 2-point lock
- ▶ 2-year standard warranty ( upgradable up to 5 years )
- ▶ TAA Compliant

**Options**

- HDMI 2.0 with 2 x USB KB/MS cable ( **HDMI** )
- 3G / HD / SD-SDI Broadcast-grade input ( **SDI** )
- DC power : 12V / 24V / 48V / 125V / 250V
- SUN Micro keyboard option
- Touchscreen :  
Projected Capacitive 10-pt / Resistive 1-pt

**Product Specifications**

Console Port	
Video input attached 6ft DP cable	Display port 1.2
KB / MS bundled 6ft USB cable x 2	USB type A

LED-backlit LCD Panel	
Panel size ( diagonal )	17.3"
Native resolution	3840 x 2160@60Hz
Brightness ( cd/m² )	400
Contrast ratio ( typ )	1000 : 1
Colors	16.7 M, 8-bit
Viewing angle ( L/R/U/D )	89/89/89/89
Response time ( ms )	16
Dot pitch ( mm )	0.0995
Display area ( mm )	382.12H x 214.94V
Surface treatment	Anti-glare
Surface hardness	3H
Backlight type	LED
MTBF ( hrs )	15,000

Physical		
Product ( W x D x H )	Single console	442 x 400 x 44 mm 17.4 x 15.7 x 1.73 inch
	Console w/ KVM	442 x 490 x 44 mm 17.4 x 19.29 x 1.73 inch
Packing ( W x D x H )	Single console	590 x 617 x 120 mm 23.2 x 24.3 x 4.7 inch
	Console w/ KVM	590 x 808 x 140 mm 23.2 x 31.8 x 5.5 inch
Net weight	Single console	8.7 kg / 19.1 lb
	Console w/ KVM	9.5 kg / 20.9 lb
Gross weight	Single console	13.7 kg / 30.2 lb
	Console w/ KVM	16.1 kg / 35.4 lb

\* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Mounting Distance	
Single console drawer	410 ~ 640 mm 16.1 ~ 25.2 inch
Console w/ KVM drawer	410 ~ 800 mm 16.1 ~ 31.5 inch

Video Option		
Digital	HDMI	HDMI 2.0 / HDCP 2.2


Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 21W / Max. 38W
	Power saving mode	Max. 2W / Max. 18W
	Power button off	Max. 1W / Nil

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	10~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

Compliance	
EMC	FCC & CE
Safety	CE / LVD & UKCA
Environment	REACH & RoHS3 / WEEE

K1417 models w/ KVM

4K 60Hz KVM	IP	Remote	8-port
	0	0	K1417 - 801K



\*\* Resolution related to LED-backlit LCD specification

4K KVM Cable

CK - 6P ( 6 ft )  
DP KVM cable

CK - 6H ( 6 ft )  
HDMI KVM cable

Resolution 16:9 - max. 3840 x 2160

Support \*\* : 16:10 - max. 1920 x 1200

4:3 - max. 1600 x 1200

Standard Keyboard

Ge

G keyboard with touchpad

Gb

G keyboard with trackball

Supporting layouts					
America					
	U.S.				
EMEA					
	U.K.	Germany	France	Russia	Spain
					Italy
	Japan	Korea			

Keyboard Options

\* US layout only

Se

S keyboard with touchpad

Sb

S keyboard with trackball

