


## Extio 3 Series

### IP KVM Extenders

Matrox Extio 3 is the world's first IP KVM extender capable of supporting 4Kp60 4:4:4 video, keyboard, mouse, USB 2.0, and audio at unprecedented low-bitrates over a standard Gigabit Ethernet network. Working as either a point-to-point or networked KVM extender, Extio 3 creates a scalable and cost-effective KVM matrix-switching environment using standard network switches. With exceptional remote performance, smooth video playback, and pristine image quality, these IP KVM extenders grant seamless remote access to secured systems, plus the added benefit of smart control over the IP network. Matrox Extio 3 was designed to ease integration and provide operational flexibility for information sharing, fast decision-making, and intuitive collaboration. Start driving KVM connections now.



## Matrox Extio 3 Series – IP KVM

Product	Part number	Form factor	Video input connectors	Video output connectors	Network interface and connector	Maximum resolutions	Stereo audio	USB 2.0 ports	RS-232	Software Available as free download
Extio N3408 Transmitter	XTO3-N3408TX	1U ½ R	1x DisplayPort 1.2 3x DisplayPort 1.1	1x DisplayPort 1.1 (local output)	1x RJ45 network port 1x SFP cage <sup>1</sup> 1,000 base-T Ethernet, auto detect, half/full duplex	1x 3840x2160 @60Hz or 2x 3840x2160 @30Hz or 2x 2560x1600 @60Hz or 4x 1920x1080 @60Hz	Analog or embedded digital audio	2	9-pin D-Type	Matrox Extio Central Manager
Extio N3408 Transmitter card	XTO3-N3408CTX	Full-height PCIe x8 card	1x Mini DisplayPort 1.2 3x Mini DisplayPort 1.1	—	1x SFP cage with RJ45 copper transceiver <sup>2</sup> 1,000 base-T Ethernet, auto detect, half/full duplex		Embedded digital audio	—		Matrox Extio Central Manager
Extio N3408 Receiver	XTO3-N3408RX	1U ½ R	—	1x DisplayPort 1.2 3x DisplayPort 1.1	1x RJ45 network port 1x SFP cage <sup>1</sup> 1,000 base-T Ethernet, auto detect, half/full duplex		Analog or embedded digital audio	6		Matrox Extio Central Manager
Extio N3208 Transmitter	XTO3-N3208TX	1U ½ R	2x DisplayPort 1.1	1x DisplayPort 1.1 (local output)	1x RJ45 network port 1x SFP cage <sup>1</sup> 1,000 base-T Ethernet, auto detect, half/full duplex	1x 2560x1600 @60Hz or 2x 1920x1200 @60Hz	Analog or embedded digital audio	2		Matrox Extio Central Manager
Extio N3208 Transmitter card	XTO3-N3208CTX	Full-height PCIe x8 card	2x Mini DisplayPort 1.1	—	1x SFP cage with RJ45 copper transceiver <sup>2</sup> 1,000 base-T Ethernet, auto detect, half/full duplex		Embedded digital audio	—		Matrox Extio Central Manager
Extio N3208 Receiver	XTO3-N3208RX	1U ½ R	—	2x DisplayPort 1.1	1x RJ45 network port 1x SFP cage <sup>1</sup> 1,000 base-T Ethernet, auto detect, half/full duplex		Analog or embedded digital audio	4		Matrox Extio Central Manager

1. Supports RJ45 copper transceiver, SFP multi-mode or single-mode transceiver (sold separately). 2. Upgradeable to fiber multi-mode or single-mode SFP transceiver (sold separately).



Extio 3 supports one-to-one, many-to-one or many-to-many configurations



Extio 3 extends up to four displays over standard Gigabit network infrastructure